

PATENT APPLICATION
Atty. Docket No. 964-991369

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of :
Bernhard GOTZ : INDUSTRIAL TRUCK WITH A
Serial No. Not Yet Assigned : REAR WEIGHT AND INTERNAL
Filed Concurrently Herewith : COMBUSTION ENGINE

Pittsburgh, Pennsylvania
October 20, 1999

LETTER RECOGNIZING ATTORNEYS

Assistant Commissioner for Patents
Washington DC 20231

Sir:

Enclosed for filing is an informal application for patent as above identified, comprising a specification, claims, abstract and drawings.

Information regarding the inventor and the application is as follows:

1. Inventors:

a) Name and Bernhard GOTZ
Residence Address: Goldregenweg 36
 63741 Aschaffenburg
Citizenship: Germany

2. Title: INDUSTRIAL TRUCK WITH A REAR WEIGHT AND INTERNAL
 COMBUSTION ENGINE

3. Drawings: 1 drawing sheet

4. Claims: 20 claims, one (1) of which is independent

5. Priority: German Application No. 198 49 753.9
 filed October 28, 1998

Please accept the application for purposes of granting a filing date and recognize William H. Logsdon, Registration No. 22,132; Blynn L. Shideler, Registration No. 35,034; and Lester N. Fortney, Registration No. 38,141 as attorneys in this


application, pending the filing of a formal Declaration and Power of Attorney and payment of the filing fee. 37 C.F.R. §1.53(f).

Kindly direct all communications relating to this application to William H. Logsdon.

Respectfully submitted,

WEBB ZIESENHEIM LOGSDON
ORKIN & HANSON, P.C.

By



William H. Logsdon
Registration No. 22,132
Attorney for Applicant
700 Koppers Building
436 Seventh Avenue
Pittsburgh, PA 15219-1818
Telephone: 412/471-8815
Facsimile: 412/471-4094

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF:

ATTORNEY'S DOCKET NUMBER

Bernhard GOTZ

964-991369

ENTITLED

"INDUSTRIAL TRUCK WITH A REAR WEIGHT AND INTERNAL
COMBUSTION ENGINE"

Box: Patent Application

Assistant Commissioner for Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

"Express Mail" Label Number EL426955686US

Date of Deposit October 20, 1999

I hereby certify that the following attached papers or fees

**Letter Recognizing Attorneys (2 pp.); Specification (5 pp.); Claims (3 pp.);
Abstract (1 p.); Drawings (1 sheet)**

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. §1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Kimberly N. Welday

(Typed name of person mailing paper or fee)

Kimberly N. Welday
(Signature of person mailing paper or fee)

A

10/20/99 1553 U.S. PRO

INDUSTRIAL TRUCK WITH A REAR WEIGHT
AND AN INTERNAL COMBUSTION ENGINE

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 This invention relates generally to an industrial truck and, more particularly, to a fork lift truck having a rear weight and an internal combustion engine.

2. Description of the Currently Available Technology

10 During the operation of an industrial truck, the internal combustion engine located in the truck generates vibrations that are frequently transmitted via the vehicle frame into other areas of the industrial truck which include, for example, the vicinity of the driver's cab. Consequently, structural noises and vibrations are
15 generated that are frequently experienced as a significant annoyance by the person in the driver's cab. The rear weight, which is usually connected to the vehicle frame of the industrial truck, represents a component that is independent of the internal combustion engine in known
20 industrial trucks.

On industrial trucks of the prior art it is customary to fasten the internal combustion engine to the vehicle frame and to use damping elements to minimize the transmission of vibrations from the engine to the frame.
25 Such a mounting of the internal combustion engine is relatively complex and expensive. Further, with this location of the internal combustion engine, it is not possible to completely isolate the various components of the industrial truck from the vibrations of the internal
30 combustion engine.

Therefore, it is an object of the invention to provide an industrial truck on which it is possible to use an easily manufactured mounting of the internal combustion engine to prevent the transmission of vibrations into
35 additional components of the industrial truck, in particular into the vicinity of the driver's cab.

SUMMARY OF THE INVENTION

The invention teaches that the above object can be accomplished by fastening the internal combustion engine to the rear weight. On account of its large mass, the rear weight can be excited to vibrate only to a very small extent by the internal combustion engine. Thus, vibrations and structural noises are not transmitted to other components that are also connected with the rear weight. This vibration-damping effect of the rear weight is reinforced by the high internal damping of the gray cast iron conventionally used for the rear weight. In addition, it is possible to pre-assemble the internal combustion engine on the rear weight, as a result of which the rear weight and the internal combustion engine can be connected in the form of a single assembly to the vehicle frame of the industrial truck.

It is particularly advantageous if the internal combustion engine is oriented in a transverse direction of the industrial truck. It is thereby possible to utilize the entire width of the industrial truck. A portion of the driver's cab of the industrial truck, for example, can therefore be located in the longitudinal space that becomes available as a result of this transverse orientation of the engine in industrial truck.

Preferably, at least one fastening means for the internal combustion engine is located on the rear weight, whereby the internal combustion engine is mounted on the fastening means so that it can oscillate. The fastening means can be connected to the rear weight by threaded fasteners. The internal combustion engine is preferably mounted on the fastening means so that it can oscillate, i.e., it has a rotational degree of freedom. In this case it is appropriate if the internal combustion engine is mounted so that it can oscillate around an axis that extends in the transverse direction of the industrial truck. The axis is thus substantially parallel to a crankshaft of the internal combustion engine. It is also

advantageous if the fastening means have an elastic damping element. The damping element reduces the vibrations that are transmitted to the rear weight. The damping elements can also be used to compensate for manufacturing tolerances of the fastening elements.

To connect the internal combustion engine with the rear weight, there is also preferably a torque support that is located at some distance from the axis. The oscillating movement of the internal combustion engine made possible by the fastening elements is limited by the torque support. The torque support also contains elastic elements, so that an oscillating movement of the internal combustion engine relative to the rear weight becomes possible.

There are additional advantages if a hydraulic unit is fastened to the internal combustion engine. The hydraulic unit, preferably a hydraulic pump, can be pre-assembled together with the internal combustion engine on the rear weight. The hydraulic unit does not require its own damping elements.

BRIEF DESCRIPTION OF THE DRAWINGS

Additional advantages and details of the invention are explained in greater detail below with reference to the exemplary embodiment illustrated in the accompanying schematic figures, in which like reference numbers indicate like parts throughout.

Fig. 1 is a side view of a rear portion of an industrial truck incorporating features of the invention; and

Fig. 2 is a plan view of the rear portion of an industrial truck incorporating features of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 shows the rear portion of an industrial truck that is configured as a fork lift truck. Fig. 1 shows a rear weight 1 as well as a steerable rear wheel 2 of the fork lift truck, which rear wheel 2 is fastened to the rear weight 1. Fig. 1 also shows a portion of a

vehicle frame 3 of the fork lift truck that is bolted to the rear weight 1. A driver's cab of the fork lift is formed from a portion of the vehicle frame 3.

5 An internal combustion engine 4 is oriented crosswise in the fork lift truck. A hydraulic unit 5 that comprises one or more hydraulic pumps is rigidly connected with the internal combustion engine 4, and forms an assembly with the latter. The internal combustion engine 4 is carried on or fastened to the rear weight 1 by fastening means 6. The fastening means 6 may be formed by 10 two pendulum bearings that permit an oscillating movement of the internal combustion engine 4 around an axis oriented substantially in the transverse direction of the fork lift truck. The fastening means 6 are equipped with elastic damping elements that at least partly absorb the vibrations generated by the internal combustion engine 4 and the hydraulic unit 5. 15

The oscillating movement of the internal combustion engine 4 is restricted by a torque support 7 which is also located between the internal combustion engine 4 and the rear weight 1. The torque support 7 is preferably also equipped with elastic damping elements. Fig. 2 shows an overhead view of the portion of the fork lift truck illustrated in Fig. 1. Fig. 2 shows in 20 particular the location of the two pendulum bearings that form the fastening means 6. The pendulum bearing shown at the top of the drawing is connected directly to a housing of the internal combustion engine 4, while the lower pendulum bearing in the drawing is fastened to the hydraulic unit 5, which for its part is rigidly connected with the internal combustion engine 4. 25 30

The internal combustion engine 4 and the hydraulic unit 5 can be pre-assembled jointly on the rear weight 1. The rear weight 1, the internal combustion engine 4 and the hydraulic unit 5 thus form a single 35 assembly, as a result of which they can be easily, quickly

and economically installed simultaneously on the vehicle frame 3.

5 It will readily be appreciated by those skilled in the art that modifications may be made to the invention without departing from the concepts disclosed in the foregoing description. Such modifications are to be considered as included within the scope of the invention. Accordingly, the particular embodiments described in detail hereinabove are illustrative only and are not limiting as
10 to the scope of the invention, which is to be given the full breadth of the appended claims and any and all equivalents thereof.

What is claimed is:

1. An industrial truck, comprising:
a rear weight; and
an internal combustion engine, wherein the
internal combustion engine is connected to the rear weight.

2. The industrial truck as claimed in claim 1,
wherein the internal combustion engine is oriented in a
substantially transverse direction of the industrial truck.

3. The industrial truck as claimed in claim 1,
including least one fastening means for the internal
combustion engine located on the rear weight, wherein the
internal combustion engine is mounted on the fastening
means such that the engine can oscillate.

4. The industrial truck as claimed in claim 1,
wherein the internal combustion engine is mounted such that
the engine can oscillate around an axis that extends in a
substantially transverse direction of the industrial truck.

5. The industrial truck as claimed in claim 3,
wherein the fastening means include an elastic damping
element.

6. The industrial truck as claimed in claim 4,
including a torque support that connects the internal
combustion engine with the rear weight, the torque support
located at a distance from the axis.

7. The industrial truck as claimed in claim 1,
including a hydraulic unit fastened to the internal
combustion engine.

8. The industrial truck as claimed in claim 2,
including at least one fastening means for the internal

combustion engine located on the rear weight, wherein the internal combustion engine is mounted on the fastening means such that the engine can oscillate.

9. The industrial truck as claimed in claim 2, wherein the internal combustion engine is mounted such that the engine can oscillate around an axis that extends in a substantially transverse direction of the industrial truck.

10. The industrial truck as claimed in claim 3, wherein the internal combustion engine is mounted such that the engine can oscillate around an axis that extends in a substantially transverse direction of the industrial truck.

11. The industrial truck as claimed in claim 4, wherein the fastening means include an elastic damping element.

12. The industrial truck as claimed in claim 9, including a torque support that connects the internal combustion engine with the rear weight, the torque support located at a distance from the axis.

13. The industrial truck as claimed in claim 10, including a torque support that connects the internal combustion engine with the rear weight, the torque support located at a distance from the axis.

14. The industrial truck as claimed in claim 11, including a torque support that connects the internal combustion engine with the rear weight, the torque support located at a distance from the axis.

15. The industrial truck as claimed in claim 2, including a hydraulic unit fastened to the internal combustion engine.

16. The industrial truck as claimed in claim 3, including a hydraulic unit fastened to the internal combustion engine.

17. The industrial truck as claimed in claim 4, including a hydraulic unit fastened to the internal combustion engine.

18. The industrial truck as claimed in claim 5, including a hydraulic unit fastened to the internal combustion engine.

19. The industrial truck as claimed in claim 6, including a hydraulic unit fastened to the internal combustion engine.


20. The industrial truck as claimed in claim 14, including a hydraulic unit fastened to the internal combustion engine.

INDUSTRIAL TRUCK WITH A REAR WEIGHT
AND AN INTERNAL COMBUSTION ENGINE

ABSTRACT OF THE INVENTION

5 An industrial truck, in particular a fork lift
truck, is provided with a rear weight and an internal
combustion engine. The internal combustion engine is
fastened to the rear weight. The internal combustion
engine is advantageously mounted so that it can oscillate
around an axis that extends in the transverse direction of
10 the industrial truck.

Fig. 1



Blatt 1/1

Fig. 2

